

Smart dry contact module

NS-PRSMD / 1 CHANNEL / ZIGBEE

Smart gate control with NETUS App connectivity and adjustable inching.


ZIGBEE 3.0

Dry contact module


SIDE

Compact profile

DRY CONTACT

COM / NO / NC relay output

INCHING MODE

Adjustable automatic switch-off

COMPACT DESIGN

39 x 39 x 19.4 mm

TECHNICAL SPECIFICATIONS

Model / product type	NS-PRSMD / 1-channel smart dry contact module
Supply	110-240 V AC, 50/60 Hz
Wireless / gateway	Zigbee 3.0; compatible NETUS gateway required
Local control / inching	S1 switch input; adjustable auto-off delay via app
Output / load rating	COM / NO / NC; 5 A; LED load 150 W
Control platform	NETUS App via a compatible NETUS gateway
Operating temperature	-10°C to +40°C
Protection / dimensions	IP20 / 39 x 39 x 19.4 mm (W x H x D)
Installation	Compact format for installation behind a wall switch. DIN rail mounting requires an additional bracket.

DIMENSIONS



GATE CONTROL APPLICATION

For gate controllers with a compatible dry-contact trigger input. Use the controller's specified contact configuration.

Inching mode turns the relay off automatically after the set delay (e.g. 2 seconds). Set the delay to suit the gate controller.