



# Matter Smart Gateway

## NS-SMG6 / MULTI-PROTOCOL / ETHERNET & WI-FI

Connect compatible smart devices for app control and home automation.



LAN / USB-C / RESET

### MULTI-PROTOCOL

Zigbee / Thread / BLE Mesh

### FLEXIBLE NETWORKING

2.4 / 5 GHz Wi-Fi + Ethernet

### DUAL POWER OPTIONS

USB-C 5 V DC or PoE

## TECHNICAL SPECIFICATIONS / MATTER GATEWAY

|                           |                                                                                                                                |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Model                     | NS-SMG6.                                                                                                                       |
| Wireless protocols        | Wi-Fi; Zigbee; Thread; Bluetooth BLE Mesh.                                                                                     |
| Wi-Fi bands               | 2.4 GHz and 5 GHz.                                                                                                             |
| Network interface         | RJ45 Ethernet, 10 / 100 Mbps; wired or wireless networking.                                                                    |
| Device / scene control    | Connect compatible sub-devices; device interconnection, automation scenes and remote viewing / control via the Smart Life app. |
| Matter / platform sharing | Matter function; sharing to compatible third-party platforms. Supported devices and functions depend on system configuration.  |
| Power supply              | USB-C: 5 V DC, 2 A; or PoE input: 48 V DC, 0.35 A. Use one power input at a time.                                              |
| Status / controls         | RGB status indicator; reset button.                                                                                            |
| Expansion                 | Reserved port for optional "4G Assistant" accessory.                                                                           |
| Operating environment     | 0-40°C; 10-90% RH, non-condensing; indoor use.                                                                                 |
| Dimensions / net weight   | 97 x 97 x 24.45 mm; approximately 139 g.                                                                                       |
| Package contents          | Gateway, power cable, network cable, power adapter, manual, mounting bracket and 2 screw packs.                                |

## INSTALLATION & SYSTEM NOTES

Connect your phone and gateway to the same network for setup in the Smart Life app. Use the supplied power adapter or a suitable PoE source. Disconnect power before fitting the optional 4G accessory.